



**CONTOUR  
CASINGS**

Contour Casings Ltd  
PO Box 125  
TELFORD  
Shropshire  
TF2 8WN

T: 01952 676 940  
F: 01952 677 043

sales@contourcasings.co.uk  
www.contourcasings.co.uk

### **Product Range - Standard Specification**

#### **Low Surface Temperature Radiator Guards Designed To Comply with NHS Guidelines.**

The Contour and Cleanline ranges of guards are strong, durable and versatile and have designed to ensure that the temperature does not exceed 43°C at a flow temperature of 80°C, in accordance with NHS Estates guidelines.

Complies with NHS Hazard Notice (96) 03 - guard will not give off toxic fumes in the event of a fire.

The guards achieve a Class 1 surface spread of flame, when tested in accordance with BS 476: Part 7, and a Class 0 fire propagation when tested in accordance with BS 476: Part 6.

The guards are supplied in one piece and are manufactured from 1.5 mm CR4 steel to BS 1449: Part 1: 1984.

Paint finish: Epoxy polyester coated, electrostatically applied to BS 4800, incorporating BioCote® anti-microbial agent to inhibit the growth of gram positive and gram negative bacteria.

Standard colour: Satin White (BS 5252F 00E 55 Matt).

Other colours: Guards can be supplied in any RAL or BS colour.

The guards are floor or wall mounted and incorporate punched top outlet and punched air inlet grilles in the front face. Grille sizes are selected to ensure that small hands cannot penetrate the casing. Guards are and there are no sharp corners. The guards are supplied complete with all cut outs for pipework and valve access - no on-site cutting is required.

#### **Dimensions:**

All guards are made to measure.

Guards are to be at least 40 mm higher than the top of the radiator, at least 60 mm deeper than the radiator's front face and 250 mm longer than the radiator.

#### Contour Guard

Fully bull nosed casing, incorporating 2 hinged side access panels for cleaning.

#### Cleanline Guard

Fully bull nosed casing and incorporating a hinged front access panel for cleaning.

#### **Contour Guard**

A range of fully bullnosed radiator guards incorporating BioCote® anti-microbial agent within the powder coated finish. Guards are supplied with hinged side access doors to facilitate simple access for routine maintenance and cleaning. Access doors are fitted with quick release security bolts, designed to be locked and unlocked quickly and easily by authorised personnel.

Heat Efficiency: Calculations estimate a variation in output between an uncovered double pane;l radiator and the same device guarded by a Contour steel radiator guard of 7%.

Standard lead time: 10 days.

Consult with Contour Casings technical literature for further details. CAD details are available upon request.

**P20/170 RADIATOR GUARDS:**

**Manufacturer:**

Contour Casings Ltd., PO Box 125, Telford, Shropshire. TF2 8WN. Tel: 01952 676 940. Fax: 01952 677 043. Email: [sales@contourcasings.co.uk](mailto:sales@contourcasings.co.uk) Web: <http://www.contourcasings.co.uk>

**Product reference:**

Contour Radiator Guard.

**Size:**

Length: . . . . . mm. (Guards in excess of 2000 mm in length are supplied in two halves of equal length)

Height: . . . . . mm.

Depth: . . . . . mm.

**Finish/Colour:**

Epoxy polyester coated electrostatically applied to BS 4800, incorporating BioCote® anti-microbial agent to inhibit the growth of gram positive and gram negative bacteria.

Standard Colour: Satin White (BS 5252F 00E 55 Matt).

Consult Contour Casings for availability of alternative colours and samples.

**Fixing:**

Floor or wall mounted using standard fixings.

**Cleanline Guard.**

A range of fully bullnosed radiator guards incorporating BioCote® anti-microbial agent within the powder coated finish. Guards are supplied with a hinged front access door to provide complete access to the interior of the radiator guard for cleaning and routine maintenance.

The access door can be laid flat on the floor or removed without the need for tools. The access door is fitted with quick release security bolts, designed to be locked and unlocked quickly and easily by authorised personnel

Standard lead time: 10 days.

Consult with Contour Casings technical literature for further details. CAD details are available upon request.

**P20/170 RADIATOR GUARDS:**

**Manufacturer:**

Contour Casings Ltd., PO Box 125, Telford, Shropshire. TF2 8WN. Tel: 01952 676 940. Fax: 01952 677 043. Email :[sales@contourcasings.co.uk](mailto:sales@contourcasings.co.uk) Web: <http://www.contourcasings.co.uk>

**Product reference:**

Cleanline Radiator Guard.

**Size:**

Length: . . . . . mm. (Guards in excess of 1200 mm in length are supplied in sections of equal length)

Height: . . . . . mm.

Depth: . . . . . mm.

**Finish/Colour:**

Epoxy polyester coated electrostatically applied to BS 4800, incorporating BioCote® anti-microbial agent to inhibit the growth of gram positive and gram negative bacteria.

Standard Colour: Satin White (BS 5252F 00E 55 Matt).

Consult Contour Casings for availability of alternative colours and samples.

**Fixing:**

Floor or wall mounted using standard fixings.